



CODE QUIZ

April 2023

1. Per Section 1010.1.3 of the 2022 CA Building Code, where door hardware operates by push or pull, the operational force to unlatch the door shall not exceed ____ pounds. Where door hardware operates by rotation, the operational force to unlatch the door shall not exceed ____ inch-pounds.
 - a. 15 pounds, 15 inch-pounds
 - b. 20 pounds, 20 inch-pounds
 - c. 15 pounds, 28 inch-pounds
2. Per Section 1031.5.2 of the 2022 CA Building Code, window area wells with a vertical depth of more than ____ inches shall be equipped with an approved permanently affixed ladder or steps. The ladder or steps shall not encroach into the required dimensions of the window well by more than ____ inches. The ladder or steps shall not be obstructed by the emergency escape and rescue opening when the window or door is in the open position.
 - a. 44 inches, 6 inches
 - b. 36 inches, 8 inches
 - c. 42 inches, 4 inches
3. Per Section 1208.4 of the 2022 CA Building Code, an efficiency dwelling unit shall have a living room of not less than ____ square feet of floor area.
 - a. 180 square feet
 - b. 190 square feet
 - c. 220 square feet
4. Per Section R301.2.2.6 of the 2022 CA Residential Code, a light-frame building or portion of a building on a hillside lot shall be designed as an irregular structure when three conditions are met one of which is that the grade slope exceeds 1 vertical in ____ horizontal where averaged across the full length of any side of the dwelling.
 - a. 4 horizontal
 - b. 5 horizontal
 - c. 6 horizontal
5. Per Section 1705.13.7 of the 2022 California Building Code, Steel storage racks and steel cantilevered storage racks that are ____ feet in height or greater and assigned to Seismic Design Category D, E or F shall be provided with periodic special inspection for their anchorage installation.
 - a. 6 feet
 - b. 8 feet
 - c. 10 feet